

# 凯瑞迪特(天津)液压器材有限公司 Tianjin Kairuidite Hydraulic Chain Co. LTD



### CONTROL

#### Manual

#### **OPTIONS**

**XQuickChange-tool** 

**XDie wall rack** 



TECHNICAL DATA		
Max crimping dia (mm)	10-61	
Max crimping dia (inches)	0.39-2.40	
Max. crimping force (kN)	1370	
Max. crimping force (tonnage)	137	
Cycle time 10 mm (s)	_	
Hose size ID (inches)	11/2	
Dies set series	P20	
Max. opening (mm)	+25	
Max.opening without dies (mm)	109	
Master die D/L (mm)	84/80	
Master die D / L (inches)	3.31/3.15	
Motor Power	Air pressure	

DIMENSIONS (L x W x H)		
Machine (mm)	600X480X480	
Machine (inch)	23.6X18.9X18.9	
Package (mm)	675X630X780	
Package (inch)	26.6X24.8X30.7	

WEIGHT (KG)	
N, W.	80
G.W.	105


## P20AP FEATURES







P20AP hose-crimping machine has been designed to crimp up to 11/2 diameter 4-spiral hoses. It is fast and easy to use. It is manually operated and compact air pressure operated model for repair and maintenance needs.



DieSetNo	Crimping range	ID (mm)	L (mm)
P20/06*	6.0 - 8.0	6	55
P20/08*	8.0 - 10.0	8	55
P20/10*	10.0 - 12.0	10	55
P20/12*	12.0 - 14.0	12	55
P20/14*	14.0 - 16.0	14	55
P20/16	16.0 - 19.0	16	55
P20/19	19.0 - 23.0	19	55
P20/23	23.0 - 27.0	23	55
P20/27	27.0 - 31.0	27	70
P20/31	31.0 - 36.0	31	70
P20/36	36.0 - 41.0	36	75
P20/41	41.0 - 47.0	41	75
P20/47	47.0 - 54.0	47	85
P20/54*	54.0 - 61.0	54	85